

W2PH Universal Antenna Switch

Configuration Call Sign:

Please answer the following questions to allow us to pre-program your UAS or to assist you in programming it yourself:

Xcvr Mfr: Flex-6xxx () Kenwood () Yaesu DB9 () Yaesu Din ()
 ICOM () Elecraft ()

ICOM Hex Code () (Only used with ICOM Radios)

Poll Xcvr: () 1 = UAS Polls (Recommended) 0 = Other source of Polling

Baudrate: () 38400 19200 9600 4800 2400 (9600 recommended)

Antenna Assignment: For each band assign an antenna 1-4 (0 = No Antenna)

	Ant 0	Ant 1	Ant 2	Ant 3	Ant 4
630m	()	()	()	()	()
160m	()	()	()	()	()
80m	()	()	()	()	()
60m	()	()	()	()	()
40m	()	()	()	()	()
30m	()	()	()	()	()
20m	()	()	()	()	()
17m	()	()	()	()	()
15m	()	()	()	()	()
12m	()	()	()	()	()
10m	()	()	()	()	()
6m	()	()	()	()	()

Please complete this form and email to ed@w2ph.com if you wish us to pre-program the unit before shipping. It is easy to modify the configuration once you have the UAS. Please direct any questions to us at (321) 574-6522 or email to the above address. Further information can be found at **w2ph.com**.